

Default Management of Guangweida Switches



AI Overview

Guangweida switches are industrial-grade managed switches that can be configured via CLI, web interface, or centralized management platforms, with default settings designed for rapid deployment and secure operation.

Accessing the Switch

Guangweida switches typically support multiple management methods:

- Web Interface:** Most models provide a local web GUI for configuration. Connect a PC to the management port and access the default IP address assigned to the switch. The default credentials are usually provided in the product documentation or on the device label.
- Command-Line Interface (CLI):** Switches can be accessed via console cable or SSH if networked. CLI commands allow detailed configuration of VLANs, QoS, PoE, and security features. Enter system-view to access the configuration mode, and use display commands to check interfaces, MAC addresses, and LLDP neighbors.
- Centralized Management:** Some models, like the GWN7806(P), support cloud or on-premise management through GDMS Networking or GWN Manager, enabling remote monitoring, firmware updates, and configuration backups.

Default Network Settings

- Management IP:** Industrial switches often ship with a default management IP, typically in the 192.168.x.x range. This allows initial access for configuration before integrating into the production network.
- VLAN:** VLAN 1 is usually the default management VLAN. It can be modified to match the network segmentation requirements.
- PoE:** For PoE-enabled models, ports may provide dynamic PoE output by default, compatible with IEEE 802.3af devices such as IP phones or cameras.

Basic Management Commands

- `display interface brief` – Shows the status of all interfaces.
- `display mac-address` – Lists MAC addresses learned by the switch.
- `display arp` – Displays the ARP table.
- `display lldp neighbor` – Shows connected LLDP-enabled...

Article Content

Smart Managed Switch Web

Smart managed switches support management via web, supporting functions such as activation and login, device overview, network configuration, device configuration, and system maintenance.

Cisco 500 Series Stackable Managed Switches Administration Guide ...

By default, the application logs out after ten minutes of inactivity. You can change this default value as described in the Defining Idle Session Timeout section.

Change ip address and default gateway on a Cisco switch

I have some switches where i need to change both ip address and default gateway on the management vlan. (remote) Is it possible to change the startup config, and reboot the switch with the

Example for Configuring Default Domain-based User Management

Example for Configuring Default Domain-based User Management Domain and Default Domain Overview The device manages access users based on domains. Each access user belongs to

How to Log into the Web User Interface (UI) of a Cisco

The objective of this document is to show you how to access the Web User Interface (UI) on a Cisco Business switch that is not on an existing

SMC_switches_QuickConfig

This document is designed to provide Supermicro switch users with the information required to configure the basic functionalities on the switch through its Web graphical user interface

Moxa Managed Ethernet Switch (UI_2.0_FW_5.x) User Manual

The Moxa switch supports the management of accounts, including establishing, activating, modifying, disabling, and removing accounts. There are two levels of configuration access: admin and user.

How to change the IP address of the smart and

If you want to change the default management IP address, you will have to go to "Routing"->"Interface ", click on "Edit" for VLAN 1, and change the IP

Switch Web

Through web or client, the switch supports status checking, port management, layer 2 configuration, and other functions. It is suitable for small-scale LAN device access.

How to Configure Router and Switch | Ultimate Guide

Table of Contents Router and Switch Configuration Benefits What Is a Switch? How to Configure Router Settings Switch and Router Configuration

TmplT-QSG

assigns a password to the admin username. assigns an IP address to the Ethernet management port. defines a default route to a network gateway. Step 1 Provide power to the switch, as described in

Huawei Switch Basic Configuration Step by Step

□□ In this video, I will show you step by step on how to configure Huawei switch using an actual device with the latest firmware version. □□ We will go through the very basic configuration,...

change ip address and default gateway

Hello DV, To change the VSM''s management ip address and gateway you must reconfigure the mgmt0 interface and appropriate ip route. For

GWN780x(P) L2+ - Quick Installation Guide

Type the switch''s default management IP address <gwn7800_IP> in the browser, and enter the username and password to log in. (The default administrator username is “admin” and

GRANDSTREAM NETWORKS GWN780 SERIES USER MANUAL

It supports advanced VLAN for flexible and sophisticated traffic segmentation, advanced QoS for prioritization of network traffic, IGMP Snooping for network performance optimization, and

Configuring the IPv4 Management Interface on

This article provides instructions on how to manually configure the IPv4 management interface (OOB) on the switch through the web-based utility.

huawei switch cheat sheet · GitHub

By default, Cisco switches use VTP version 2, while Huawei switches use VTP version 3. If the VTP configuration is not compatible between the two types of switches, it can cause problems

What should I do if I cannot access the web

For how to use the command line, please refer to the User Guide of the switch. Management VLAN is only supported on T1500 series switches;

Typical Login Configuration

Configure the domain huawei as the default global management domain so that an administrator does not need to enter the domain name for logging in to the Switch.

GWN7806(P) – Quick Installation Guide

GWN7806 (P) is easy to deploy and manage, including managed by the local Web user interface of the GWN7806 (P) switch and CLI, the command-line interface. The switch is also

Huawei network switch S1700

While making an ICT inventory in an organization I came across a network switch that seems to be locked-down. This organization has a Huawei network switch 1700 series.

What Is the Default Login Password?

What Is the Default Login Password? The default username and password are available in S Series Switches Default Usernames and Passwords (Enterprise Network or Carrier). If you have not

How to change the IP address of the smart and managed switches

If you want to change the default management IP address, you will have to go to "Routing"->"Interface ", click on "Edit" for VLAN 1, and change the IP address and Subnet Mask.

GWN781x(P) – Quick Installation Guide

OVERVIEW The GWN781x(P) series are Layer 3 managed network switches that allow medium-to-large enterprises to build scalable, secure, high performance and smart business

How to configure Management VLANs for Omada Switches and APs

Contents Introduction Requirements Configuration Verification Conclusion

Introduction This article will configure separate management VLAN for switches and APs, and keep the default

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.introspec.co.za>

Email: info@introspec.co.za

Phone: +27 73 849 2156

Address: 25 Riebeek Street, Cape Town, 8001, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

